

Package: multDM (via r-universe)

October 17, 2024

Type Package

Title Multivariate Version of the Diebold-Mariano Test

Version 1.1.4

Imports MTS

Date 2022-06-09

Author Krzysztof Drachal [aut, cre] (Faculty of Economic Sciences,
University of Warsaw, Poland)

Maintainer Krzysztof Drachal <kdrachal@wne.uw.edu.pl>

Description Allows to perform the multivariate version of the
Diebold-Mariano test for equal predictive ability of multiple
forecast comparison. Main reference: Mariano, R.S., Preve, D.
(2012) <doi:10.1016/j.jeconom.2012.01.014>.

License GPL-3

LazyData TRUE

URL <https://CRAN.R-project.org/package=multDM>

Note Research funded by the Polish National Science Centre grant under
the contract number DEC-2015/19/N/HS4/00205.

NeedsCompilation no

Date/Publication 2022-06-09 09:50:08 UTC

Repository <https://kdrachal.r-universe.dev>

RemoteUrl <https://github.com/cran/multDM>

RemoteRef HEAD

RemoteSha e87f4bd921f6e55fdf66b6ba8684d7b26517907a

Contents

DM.test	2
d_t	3
loss	4
MDM.selection	5

MDM.test	6
MDMforecasts	7
oilforecasts	8
print.MDM	10
TB_AR_test	10
TB_MA	11
Index	13

DM.test	<i>Computes Diebold-Mariano Test for the Equal Predictive Accuracy.</i>
---------	---

Description

This function computes Diebold-Mariano test for the equal predictive accuracy. The null hypothesis of this test is that two forecasts have the same accuracy. The alternative hypothesis can be specified as "Both forecasts have different accuracy", "The first forecast is less accurate than the second forecast", or "The first forecast is more accurate than the second forecast".

Usage

```
DM.test(f1, f2, y, loss.type="SE", h, c=FALSE, H1="same")
```

Arguments

f1	vector of the first forecast
f2	vector of the second forecast
y	vector of the real values of the modelled time-series
loss.type	method to compute the loss function, loss.type="SE" will use squared errors, loss.type="AE" will use absolute errors, loss.type="SPE" will use squared proportional error (useful if errors are heteroskedastic), loss.type="ASE" will use absolute scaled error, if loss.type will be specified as some numeric , then the function of type $\exp(\text{loss.type} \times \text{errors}) - 1 - \text{loss.type} \times \text{errors}$ will be used (useful when it is more costly to underpredict y than to overpredict), if not specified loss.type="SE" is used
h	numeric denoting that the forecast h-steps ahead are evaluated, if not specified h=1 is used
c	logical indicating if Harvey-Leybourne-Newbold correction for small samples should be used, if not specified c=FALSE is used
H1	alternative hypothesis, H1="same" for "both forecasts have different accuracy", H1="more" for "the first forecast is more accurate than the second forecast", H1="less" for "the first forecast is less accurate than the second forecast", if not specified H1="same" is taken

Value

class htest object, [list](#) of

statistic	test statistic
parameter	h, forecast horizon used
alternative	alternative hypothesis of the test
p.value	p-value
method	name of the test
data.name	names of the tested time-series

References

Diebold, F.X., Mariano, R. 1995. Comparing predictive accuracy. *Journal of Business and Economic Statistics* **13**, 253–265.

Harvey, D., Leybourne, S., Newbold, P., 1997. Testing the equality of prediction mean squared errors. *International Journal of Forecasting* **13**, 281–291.

Hyndman, R.J., Koehler, A.B. 2006. Another look at measures of forecast accuracy. *International Journal of Forecasting* **22**, 679–688.

Taylor, S. J., 2005. *Asset Price Dynamics, Volatility, and Prediction*, Princeton University Press.

Triacca, U., 2018. *Comparing Predictive Accuracy of Two Forecasts*, <https://www.lem.sssup.it/phd/documents/Lesson19.pdf>.

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
DM.test(f1=forecasts[,1], f2=forecasts[,2], y=ts, loss="SE", h=1, c=FALSE, H1="same")
```

d_t	<i>Computes Loss Differential.</i>
-----	------------------------------------

Description

This function computes loss differential, i.e., differences between losses from $k + 1$ -th and k -th models.

Usage

```
d_t(e)
```

Arguments

e [matrix](#) of loss functions, columns correspond to time index, and rows to different models

Value

`matrix` of loss differentials

References

Mariano R.S., Preve, D., 2012. Statistical tests for multiple forecast comparison. *Journal of Econometrics* **169**, 123–130.

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
l <- loss(realized=ts,evaluated=forecasts,loss.type="SE")
d <- d_t(l)
```

loss	<i>Computes Loss Function.</i>
------	--------------------------------

Description

This function computes various loss functions for given realized values of time-series and a collection of forecasts.

Usage

```
loss(realized,evaluated,loss.type)
```

Arguments

realized	<code>vector</code> of the real values of the modelled time-series
evaluated	<code>matrix</code> of the forecasts, columns correspond to time index, rows correspond to different models
loss.type	method to compute the loss function, <code>loss.type="SE"</code> will use squared errors, <code>loss.type="AE"</code> will use absolute errors, <code>loss.type="SPE"</code> will use squared proportional error (useful if errors are heteroskedastic), <code>loss.type="ASE"</code> will use absolute scaled error, if <code>loss.type</code> will be specified as some <code>numeric</code> , then the function of type $\exp(\text{loss.type} \times \text{errors}) - 1 - \text{loss.type} \times \text{errors}$ will be used (useful when it is more costly to underpredict realized than to overpredict)

Value

`matrix` with columns corresponding to time index and rows to different models

References

- Hyndman, R.J., Koehler, A.B. 2006. Another look at measures of forecast accuracy. *International Journal of Forecasting* **22**, 679–688.
- Taylor, S. J., 2005. *Asset Price Dynamics, Volatility, and Prediction*, Princeton University Press.
- Triacca, U., 2018. *Comparing Predictive Accuracy of Two Forecasts*, <https://www.lem.sssup.it/phd/documents/Lesson19.pdf>.

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
l <- loss(realized=ts,evaluated=forecasts,loss.type="SE")
```

MDM.selection	<i>Selects Models with Outstanding Predictive Ability basing on Multivariate Diebold-Mariano Test.</i>
---------------	--

Description

This function selects models with outstanding predictive ability basing on multivariate Diebold-Mariano test [MDM.test](#).

Usage

```
MDM.selection(realized,evaluated,q,alpha,statistic="Sc",loss.type="SE")
```

Arguments

realized	vector of the real values of the modelled time-series
evaluated	matrix of the forecasts, columns correspond to time index, rows correspond to different models
q	numeric indicating a lag length beyond which we are willing to assume that the autocorrelation of loss differentials is essentially zero
alpha	numeric indicating a significance level for multivariate Diebold-Mariano tests
statistic	statistic="S" for the basic version of the test, and statistic="Sc" for the finite-sample correction, if not specified statistic="Sc" is used
loss.type	method to compute the loss function, loss.type="SE" will use squared errors, loss.type="AE" will use absolute errors, loss.type="SPE" will use squared proportional error (useful if errors are heteroskedastic), loss.type="ASE" will use absolute scaled error, if loss.type will be specified as some numeric , then the function of type $\exp(\text{loss.type} \cdot \text{errors}) - 1 - \text{loss.type} \cdot \text{errors}$ will be used (useful when it is more costly to underpredict realized than to overpredict), if not specified loss.type="SE" is used

Value

class MDM object, **list** of

outcomes **matrix** with mean losses for the selected models, statistics corresponding to losses differentials and ranking of these statistics

p.value **numeric** of p-value from the procedure, i.e., p-value of multivariate Diebold-Mariano test from the last step

alpha alpha, i.e., the chosen significance level

eliminated **numeric** indicating the number of eliminated models

References

Mariano R.S., Preve, D., 2012. Statistical tests for multiple forecast comparison. *Journal of Econometrics* **169**, 123–130.

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
MDM.selection(realized=ts,evaluated=forecasts,q=10,alpha=0.1,statistic="S",loss.type="AE")
```

MDM.test	<i>Computes Multivariate Diebold-Mariano Test for the Equal Predictive Accuracy of Two or More Non-nested Forecasting Models.</i>
----------	---

Description

This function computes multivariate Diebold-Mariano test for the equal predictive accuracy of two or more non-nested forecasting models. The null hypothesis of this test is that the evaluated forecasts have the same accuracy. The alternative hypothesis is that Equal predictive accuracy (EPA) does not hold.

Usage

```
MDM.test(realized,evaluated,q,statistic="Sc",loss.type="SE")
```

Arguments

realized **vector** of the real values of the modelled time-series

evaluated **matrix** of the forecasts, columns correspond to time index, rows correspond to different models

q **numeric** indicating a lag length beyond which we are willing to assume that the autocorrelation of loss differentials is essentially zero

statistic **statistic="S"** for the basic version of the test, and **statistic="Sc"** for the finite-sample correction, if not specified **statistic="Sc"** is used

`loss.type` method to compute the loss function, `loss.type="SE"` will use squared errors, `loss.type="AE"` will use absolute errors, `loss.type="SPE"` will use squared proportional error (useful if errors are heteroskedastic), `loss.type="ASE"` will use absolute scaled error, if `loss.type` will be specified as some `numeric`, then the function of type $\exp(\text{loss.type} \times \text{errors}) - 1 - \text{loss.type} \times \text{errors}$ will be used (useful when it is more costly to underpredict realized than to overpredict), if not specified `loss.type="SE"` is used

Value

class `htest` object, `list` of

<code>statistic</code>	test statistic
<code>parameter</code>	<code>q</code> , a lag length
<code>alternative</code>	alternative hypothesis of the test
<code>p.value</code>	p-value
<code>method</code>	name of the test
<code>data.name</code>	names of the tested objects

References

Mariano R.S., Preve, D., 2012. Statistical tests for multiple forecast comparison. *Journal of Econometrics* **169**, 123–130.

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
MDM.test(realized=ts,evaluated=forecasts,q=10,statistic="S",loss.type="AE")
```

MDMforecasts

Sample Data.

Description

Sample artificial data.

Usage

```
data(MDMforecasts)
```

Format

`MDMforecasts` is `list` object such that

`MDMforecasts$ts` is `vector` of time-series which is of interest to model

- `MDMforecasts$forecasts` is `matrix` of 20 different forecasts of `ts` from 20 different forecasting models, each row represents different forecast and time is indexed by columns

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
MDM.test(realized=ts,evaluated=forecasts,q=10,statistic="S",loss.type="AE")
```

oilforecasts

Sample Data from Crude Oil Price Forecasting.

Description

Forecasts obtained from various methods applied to crude oil price.

Usage

```
data(oilforecasts)
```

Format

oilforecasts is `matrix` object such that its rows correspond to forecasts from various methods, i.e.,

REALIZED is the forecasted time-series,

- DMA.DOW is the forecast from Dynamic Model Averaging with the dynamic Occam's window,
- BMA.DOW is the forecast from Bayesian Model Averaging with the dynamic Occam's window,
- DMA.1V is the forecast from Dynamic Model Averaging applied only to one-variable models,
- BMA.1V is the forecast from Bayesian Model Averaging applied only to one-variable models,
- DMS.1V is the forecast from Dynamic Model Selection applied only to one-variable models,
- BMS.1V is the forecast from Bayesian Model Selection applied only to one-variable models,
- TVP is the forecast from Time-Varying Parameters regression,
- LASSO is the forecast from LASSO regression,
- RIDGE is the forecast from RIDGE regression,
- DYN.EL.NET is the forecast from the elastic net regression, with the elastic net mixing parameter changing with time index,
- LARS is the forecast from the least-angle regression,
- B.LASSO is the forecast from the Bayesian LASSO regression,
- B.RIDGE is the forecast from the Bayesian RIDGE regression,
- ARIMA is the forecast from the best ARIMA model according to AIC,
- NAIVE is the naive forecast, i.e., the last observation is taken as a one-step ahead prediction,
- MA is the moving average.

Details

The data were taken from Juvenal and Petrella (2015). They cover the period between 1971 and 2009, and are in quarterly frequency. Time-series with missing observations were excluded from the original data set, resulting finally in 127 explanatory variables, instead of 150 in the original data set. In particular, the excluded time-series are the ones which start date is after 1971. The dependent time-series is the average world price of oil taken in logarithmic differences. The independent time-series represent various stationarity transformations of macroeconomic and financial variables of the G7 countries and from the oil market, global economic activity and various commodity prices. The details of the original data set are given in the paper by Juvenal and Petrella (2015). The forecasting with various models, based on this data set, was done by the author of this package, just to provide some more concrete example set of forecasts. The independent variables were taken in the first lags. The forgetting parameters in DMA/DMS models were set to 0.99, resulting in the effective rolling window size of 100. Therefore, such a window was taken for the moving average. LASSO and RIDGE (also in the Bayesian versions), the elastic net, the least-angle regression and ARIMA models were estimated in rolling windows of the size of 100 observations. First 100 observations were excluded, and `oilforecasts` consists of the remaining last observations. The estimations were done with the following packages `fdMA`, `forecast`, `glmnet`, `lars` and `monomvn`.

References

- Drachal, K. 2017. `fdMA`: Dynamic Model Averaging and Dynamic Model Selection for continuous outcomes. <https://CRAN.R-project.org/package=fdMA>
- Friedman, J., Hastie, T., Tibshirani, R. 2010. Regularization paths for generalized linear models via coordinate descent. *Journal of Statistical Software* **33**, 1–22.
- Gramacy, R.B. 2017. `monomvn`: Estimation for Multivariate Normal and Student-t Data with Monotone Missingness. <https://CRAN.R-project.org/package=monomvn>
- Hastie, T., Efron, B. 2013. `lars`: Least Angle Regression, Lasso and Forward Stagewise. <https://CRAN.R-project.org/package=lars>
- Hyndman, R.J., Khandakar, Y. 2008. Automatic time series forecasting: the `forecast` package for R. *Journal of Statistical Software* **26**, 1–22.
- Juvenal, L., Petrella, I. 2015. Speculation in the oil market. *Journal of Applied Econometrics* **30**, 612–649.

Examples

```
data(oilforecasts)
ts <- oilforecasts[1,]
forecasts <- oilforecasts[-1,]
l <- loss(realized=ts,evaluated=forecasts,loss.type="SE")
d <- d_t(l)
q <- TB_MA(d=d,q.max=4)
MDM.selection(realized=ts,evaluated=forecasts,q=q,alpha=0.1,statistic="Sc",loss.type="SE")
```

```
print.MDM          Prints MDM Object.
```

Description

The function prints selected outcomes obtained from [MDM.selection](#).

Usage

```
## S3 method for class 'MDM'
print(x, ...)
```

Arguments

```
x          an object of MDM class
...        not used
```

Details

The function prints models with outstanding predictive ability, their mean loss function, statistics corresponding to their loss differentials (they are the number of the models less one), and orders these statistics. It also prints the p-value of the test and the number of eliminated models. If no models with outstanding predictive ability were found, the function prints such an information.

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
m <- MDM.selection(realized=ts,evaluated=forecasts,q=10,alpha=0.1,statistic="S",loss.type="AE")
print(m)
```

```
TB_AR_test          Computes Tiao-Box Test for Autocorrelation.
```

Description

This function computes Tiao-Box test for autocorrelation, i.e, coefficient of p-th lag in VAR(p) model. Its null hypothesis is that p-th lag is not essential. The alternative hypothesis is that it is essential.

Usage

```
TB_AR_test(d,p)
```

Arguments

- d [matrix](#) of time-series, assumed to be the stationary VARMA type, columns correspond to time index, and rows to different time-series
- p [numeric](#) indicating a lag length beyond which we are willing to assume that the autocorrelation is essentially zero

Value

- class htest object, [list](#) of
- statistic test statistic
- parameter q, a lag length
- alternative alternative hypothesis of the test
- p.value p-value
- method name of the test
- data.name name of the tested time-series

References

Tiao, G.C., Box, G.E.P. 1981. Modeling multiple times series with applications. *Journal of the American Statistical Association* **76**, 802–816.

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
l <- loss(realized=ts,evaluated=forecasts,loss.type="SE")
d <- d_t(1)
TB_AR_test(d=d,p=10)
```

 TB_MA

Checks for a Lag in VMA Process with Tiao-Box Procedure.

Description

This function helps to find a lag in stationary VMA process with Tiao-Box procedure, i.e., the lag length beyond which we are willing to assume that the autocorrelation is essentially zero.

Usage

```
TB_MA(d, q.max)
```

Arguments

- `d` [matrix](#) of time-series, assumed to be the stationary VARMA type, columns correspond to time index, and rows to different time-series
- `q.max` [numeric](#) indicating the maximum number of lag to be considered

Details

The function searches for correlations smaller than $-2n^{-0.5}$ or higher than $2n^{-0.5}$, where n is the length of the time-series.

Value

[numeric](#) indicating the found lag length

References

Tiao, G.C., Box, G.E.P. 1981. Modeling multiple times series with applications. *Journal of the American Statistical Association* **76**, 802–816.

Examples

```
data(MDMforecasts)
ts <- MDMforecasts$ts
forecasts <- MDMforecasts$forecasts
l <- loss(realized=ts,evaluated=forecasts,loss.type="SE")
d <- d_t(1)
TB_MA(d=d,q.max=10)
```

Index

d_t, 3

DM.test, 2

list, 3, 6, 7, 11

logical, 2

loss, 4

matrix, 3–8, 11, 12

MDM.selection, 5, 10

MDM.test, 5, 6

MDMforecasts, 7

numeric, 2, 4–7, 11, 12

oilforecasts, 8

print.MDM, 10

TB_AR_test, 10

TB_MA, 11

vector, 2, 4–7